



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 9450°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20305-24B	x = .285 y = .289	1750 @ 0°C	780	5 ± 1	35,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p>				
			<p>TITLE</p> <p>MINIATURE COLD CATHODE FLUORESCENT LAMP</p>						
<p>B RATED LIFE HRS MINIMUM 7/30/09</p> <p>A START VOLT TO 2600 & OPER VOLT TO 1400 8/23/07</p> <p>RELEASED 12/5/05</p>			<p>DRAWN BY L. WENGSTROM</p> <p>APPV'D BY L.R. DATE 7/30/09</p>		<p>SIZE A</p>	<p>FSCM NO. 55335</p>	<p>DRAWING NO. BF20305-24B</p>		
<p>REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE</p>			<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>		<p>SCALE NONE</p>	<p>RELEASED DATE 12/5/05</p>	<p>REVISION DATE 7/30/09</p>	<p>REV. NO. B</p>	<p>SHEET 1 OF 1</p>